

New



Design hardware with concealed sliding technology

HAWA-Purolino-PLUS 80




Maximum transparency and ideal functionality for your all-glass sliding doors, with options for soft closing and fixed glass elements.

HAWA-Purolino-PLUS 80


A decision for glass doors expresses a desire for transparency, light and a clear view. Anyone looking for sliding hardware that emphasises these properties could do no better than to choose the HAWA-Purolino-PLUS 80. All of the technical components of this sophisticated designer hardware are invisibly concealed in the top track. It can be mounted to the wall or ceiling or integrated in the ceiling. In combination with fixed glass elements, it offers attractive design options for virtually any structural situation. It is therefore equally at home in high end residential buildings as it is in hotels and elegant business premises.

About the product


The HAWA-Purolino-PLUS 80 is invisible, although its technical qualities are clearly obvious. Take, for instance, the smooth running properties owed to a high-quality trolley. Particularly pleasing: the gentle door deceleration by the SoftMove 80 soft closing mechanism that pulls the doors softly and silently into the end position. Its convenience starts with installation. The innovative wedge suspension and the trolley are simply integrated to the already installed top track.




Wall mounting.




Ceiling mounting without fixed glass.



Ceiling mounting with a fixed glass profile.



Integrated ceiling mounting without fixed glass.



Integrated ceiling mounting with a fixed glass profile.

Technical Specifications

Max. door weight 80 kg (176 lbs.)

Min. door width

without SoftMove 80 600 mm
(1'11 ⁵/₈")

with SoftMove 80 850 mm
(2'9 ¹⁵/₃₂")

Glass thickness of sliding door

ESG* 8/10/12/12,7 mm
(⁵/₁₆" / ¹³/₃₂" / ¹⁵/₃₂" / ¹/₂")

VSG** 8-12,7 mm
(⁵/₁₆" - ¹/₂")

Glass thickness for stationary glass

ESG*/VSG** 8-12 mm (⁵/₁₆" - ¹⁵/₃₂")
(with silicon up to 13 mm (¹⁷/₃₂"))

Height adjustable ±3 mm (¹/₈")

* fully tempered monolithic glass

** fully tempered laminated glass

At a glance

- Glass retention technology completely integrated in the top track.
- Top track, fixed glass and cover profiles available in alu plain anodized or stainless steel effect.
- Patent-pending wedge suspension for trouble-free installation and quick and easy height adjustment.
- Form-fitting, stable connections between hardware and glass provide high operational safety.
- Gentle door deceleration by an optional SoftMove 80 soft closing mechanism with a hydraulic oil damper.

Further information:

Hawa AG
8932 Mettmenstetten
Switzerland
Tel. +41 44 767 91 91
Fax +41 44 767 91 78
www.hawa.ch



Available from specialist dealers